



CH 05 - PRESTAZIONI CON MOTORI A 4 POLI 1400 GIRI ENTRATA

| TIPO | i=ratio | n2 r/min | Kw=P1 | Nm=T2 | f.s. | Pred. attacco motore possibili | |
|-------|---------|----------|-------|-------|------|--------------------------------|--------|
| CH 05 | 7 | 200 | 1.1* | 40 | 1.4 | 80/71 | B5/B14 |
| | 10 | 140 | 1.1* | 49 | 1.2 | 80/71 | B5/B14 |
| | 14 | 100 | 0.75 | 57 | 1.1 | 80/71 | B5/B14 |
| | 18 | 78 | 0.55 | 52 | 1.1 | 80/71 | B5/B14 |
| | 24 | 58 | 0.55 | 67 | 0.9 | 80/71 | B5/B14 |
| | 28 | 50 | 0.55 | 73 | 1.0 | 80/71 | B5/B14 |
| | 36 | 39 | 0.37 | 61 | 1.1 | 71 | B5/B14 |
| | 45 | 31 | 0.37 | 65 | 0.9 | 71/63 | B5/B14 |
| | 60 | 23 | 0.25 | 60 | 1.0 | 71/63 | B5/B14 |
| | 70 | 20 | 0.22 | 55 | 0.9 | 63 | B5/B14 |
| | 80 | 17 | 0.18 | 54 | 1.0 | 63 | B5/B14 |
| | 100 | 14 | 0.18 | 50 | 0.9 | 63 | B5/B14 |

* Motori gr. 80

Peso Kg 3

DIMENSIONI

